MS-WP-SS-ATEX

Explosion Proof Water Pump Kit

















Features

- CNEX explosion proof certificate
- 316L Stainless Steel
- 4.5 metres water pump lift head, aluminium alloy material
- Water pressure flow :1.2L/min
- The liquid in the kettle must keep noncondensing when the temperature is -20°C
- The altitude heights between the pump's outlet port and the spray nozzle must be lower than 4.5 metres.
- IP66 protection level

Business Opportunities

MS-WP-SS-ATEX is a explosion-proof water pump kit, optional accessries for MoviSight explosion-proof series products. It consists of cabinet, pump, kettle and other accessories. User can control this water pump to spray water with the spray nozzle installed on explosion proof camera and clean the camera lens through software or commands. After our reduplicated tests, this product is tough enough to withstand most severe environment challenge. Especially in dust environment.

Products Advantages


The Explosion-Proof pump is used for hazardous Zone1 and Zone2 which contains class IIA、IIB and IIC volatile gas, as well as other hazardous location, like Zone21 and Zone22. For those cameras which are equipped with wiper, it can spray water to the window glass for cleaning.

MS-WP-SS-ATEX is made of 316L stainless steel, and its protection level is IP66.

Technical Specifications

o o o o o o o o o o o o o o o o o o o			
Cabinet			
Material	316L Stainless Steel		
Thickness	1.2mm		
Dimensions (L x W x H mm)	410 (L)x145(W)x415 (H)		
Weight	5.75Kg		
Kettle			
Material	PE		
Dimensions (L x W x H mm)	180(L)x130(W)x290(H)		
Capacity	5.0L		
Spary Nozzle			
Material	316L Stainless Steel		
Nozzle Outlet	Ф1.5 mm		
Waterpipe			
Dimension	Ф4mm (internal diameter) -Ф6mm (external diameter)Х 6m		
Material	PTFE		
Explosion-Proof Water Pump			
Material	2A12 aluminum alloy		
Thickness	12mm		
Weight	1.75kg		
Protection Level	IP66		
Working temperature	-20°C~+60°C		
Atmospheric Pressure	86~106kPa		
Power Supply	DC12V		
Power Consumption	36W		
Lift Head	4.5m		
Water Suction Head	0m		
Liquid Flow Rate	1.2 L/min		

Dimension (mm)



EXPLOSION PROOF ACCESSORIES

EXI EGGION I NOO! AGGEG	OOKIEO	
MS7002SS-WMA Explosion Pro	oof Housing Wall-Mount Bracket	
Meterial	316L stainless steel	
Thickness	2.5mm	
Weight	2.8Kg	
Load Weight	45Kg	
Dimensions (L x W x H mm)	343x210x200	
MS7030SS-WMA Explosion Pro	oof PTZ Camera Wall-Mount Bracket	
Meterial	316L stainless steel	
Thickness	4.5mm	
Weight	6.8Kg	
Load Weight	90Kg	
Dimensions (L x W x H mm)	290x180x130	v
MS7000SS-CMA Explosion Pro	of Cornor Mount Braket	
Meterial	316L stainless steel	
Thickness	4.5mm	
Weight	5Kg	
Load Weight	90Kg	
Dimensions (L x W x H mm)	396x180x215	
MS7000SS-PMA Explosion Pro	of Pole Mount Bracket	
Meterial	316L stainless steel	
Thickness	4.5mm	9
Weight	1.8Kg	-0 1
Load Weight	90Kg	
Dimensions (L x W x H mm)	210x160x45	
	4	

MoviSight_®

for more information, please visit www.movisight.com